

IN THE CLAIMS AMEND

1. Cancelled

2. (Currently Amended) ~~The male coupling portion of Claim 1 wherein:~~ A male coupling portion of the type configured for use with a female coupling portion to form a fluid-flow coupling structure, each of the male and female coupling portions defining a respective fluid flow path and being removably engageable with one another to communicate the respective fluid flow paths, each coupling portion including a respective valve element having a respective closed first position closing the respective fluid flow path from ambient, said respective valve elements moving to respective open second positions when said coupling portions are engaged together to communicate said fluid flow paths with one another, said male coupling portion comprising:

- a guide structure including support means for supportingly and releasably engaging onto the female coupling portion;

- said guide structure including structure for guiding a male probe portion in reciprocation between a first position disengaged from the female coupling portion and a second position in which said male probe portion is engageable into the female coupling portion when said coupling portions are engaged together said guide structure includes a pair of diametrically opposite axially extending and arcuate guide tangs;

- a said male probe portion reciprocable on said guide structure and carrying said respective valve element of said male coupling portion, and said guide structure and respective valve element including cooperating structure for moving said respective valve element to its

open second position in response to reciprocation of said male probe portion to its said second position;

_____ - an actuator rotationally carried upon said guide structure, said actuator and said male probe portion defining cooperating structure for reciprocating said male probe portion between its said first position and its said second position in response to rotation of said actuator.

3. (Original) The male coupling portion of Claim 2 wherein said pair of axially extending arcuate guide tangs cooperatively define a substantially circular passage slidably receiving said male probe portion.

4. (Original) The male coupling portion of Claim 2 wherein said pair of axially extending arcuate guide tangs each define a pair of circumferentially opposite and axially extending side edges, each side edge of said pair of arcuate guide tangs being in circumferential confrontation with a side edge of the other of said pair of arcuate guide tangs to define an axially extending slot.

5. (Original) The male coupling portion of Claim 4 further including said male probe portion carrying a nut member reciprocating with said male probe portion, said nut member including a protrusion extending radially into said axially extending slot and slidably engaging with said circumferentially confronting side edges of said guide tangs to prevent relative rotation of said nut member while allowing axial relative movement.

6. (Original) The male coupling portion of Claim 5 wherein said cooperating structure of said actuator and said male probe portion includes said protrusion carrying a section of interrupted male thread radially outwardly disposed on a radially outer surface of the protrusion, said interrupted thread threadably engaging a female thread defined on an inner surface of said actuator member.

7. (Original) The male coupling portion of Claim 6 wherein said nut member includes a pair of diametrically opposite protrusions, each of said pair of protrusions carrying a respective one of a pair of interrupted male thread sections, and said actuator member includes a double-start thread engaging each of said pair of interrupted thread sections.

8. (Currently Amended) The male coupling portion of Claim 4 wherein said ~~guide portion~~ structure and said actuator member further define cooperating structure for allowing relative rotation of said actuator member while preventing axial relative movement.

9. (Original) The male coupling portion of Claim 8 wherein said cooperating structure of said guide portion and said actuator includes said guide portion defining a radially and circumferentially extending groove, said actuator including a radially and circumferentially extending rib received rotationally into said groove and preventing axial relative movement of said actuator on said guide portion.

10. (Original) The male coupling portion of Claim 9 wherein said guide portion includes a reentrant collar portion cooperating with a remainder portion of said guide portion to define an

axially extending groove, said collar portion defining said radially and circumferentially extending groove of said guide portion.

11. (Currently Amended) The male coupling portion of Claim 1 wherein said cooperating structure of said guide structure and respective valve element for moving said respective valve element to its open second position in response to reciprocation of said male probe portion to its said second position includes said respective valve element being of generally tubular configuration and being slidably received on said male probe portion, said valve element further defining a radially outwardly extending flange engaging said guide ~~portion~~ structure upon reciprocation of said male probe portion to its second position.

12. (Original) The male coupling portion of Claim 4 further including said male probe portion carrying a thrust collar member reciprocating with said male probe portion, said thrust collar member and said actuator member including cooperating structure for transferring axial force therebetween while allowing relative rotation so that said thrust collar moves axially in unison with said actuator member.

13. (Original) The male coupling portion of Claim 12 wherein said cooperating structure of said thrust collar member and of said actuator includes said thrust collar having a pair of radially outwardly extending protrusions, and said actuator including a pair of axially spaced apart radially extending flanges receiving said protrusions therebetween.

14. (Currently Amended) The male coupling portion of Claim 4 wherein said guide ~~portion~~ structure and said actuator member further define cooperating structure for allowing relative rotation of said actuator member while simultaneously causing axial relative movement.

15. (Original) The male coupling portion of Claim 14 wherein said cooperating structure of said guide portion and said actuator member includes said guide portion defining a male thread and said actuator including a female thread threadably engaging said male thread so that said actuator moves axially along said guide portion in response to relative rotation to transfer axial force to anon-rotational thrust collar.

16. (Original) The male coupling portion of Claim 15 wherein said actuator includes a tubular portion received into said axial passage of said guide portion, said tubular portion and thrust collar defining cooperating structure for allowing relative rotation of said actuator member while transferring axial force to said thrust collar.

17. (Currently Amended) The male coupling portion of Claim 1 ~~2~~ wherein said respective valve member of said male coupling portion includes a sealing sleeve member which is slidably carried on said male probe portion, said male probe portion defining an axially extending part of said respective fluid flow path of said male coupling portion and also defining an aperture opening laterally outwardly thereon, said sealing sleeve member in said closed first position spanning and closing said aperture, said sealing sleeve member including a radially outwardly extending element engageable with said guide ~~portion~~ structure upon forward reciprocation of said male probe portion to stop further forward motion of said sealing sleeve member so that said

male probe portion continues forward toward said female coupling portion to uncover said aperture.

18. (Currently Amended) A coupling structure with male and female coupling structure portions each defining a fluid flow path, and each removably engageable with the other to open fluid communication therebetween, and said coupling portions also being disengageable from one another to close communication between each fluid flow path and ambient, each one of the male and female portions of the having a respective movable valve member in a first position closing communication with ambient and in a second position opening communication between the fluid flow paths of the engaged coupling portions, the male coupling portion comprising:

- a guide structure including support structure for releasably engaging onto the female coupling portion so that the fluid flow passages of each coupling portion are axially aligned, said guide structure including structure for guiding a male probe portion in reciprocation between a first position disengaged from the female coupling portion and in which the respective valve member is in its closed first position and a second position in which said male probe portion is engaged into the female coupling portion and both said respective valve members are moved to their opened second positions, the guide structure including a pair of diametrically opposite axially extending and arcuate guide tangs;

- said male probe portion being reciprocable on said guide structure and carrying said respective valve element of said male coupling portion, and said guide structure and respective valve element including cooperating structure for moving said respective valve element axially

of said male probe portion to its open second position in response to reciprocation of said male probe portion to its said second position relative to said guide structure; and

- an actuator rotationally carried upon said guide structure, said actuator and said male probe portion defining cooperating structure for reciprocating said male probe portion between its said first position and its said second position in response to rotation of said actuator relative to said guide structure.

19. – 22. Cancelled.